

Heavy Vehicle Specialist Certificate

Heavy Vehicle Specialist Inspector and Inspecting Organisation

Heavy Vehicle Specialist Inspector's Name (PRINT IN CAPS) BRUCE SUTTON			BJS
Vehicle Registration*	VIN / Chassis N	lumber E 2 0 0 1 6 D	1023129
Component being certified: Certification Category HUS2	62064	Modification Load Anci	Log Bolsters
Description of Work Certify	SRT-	Saxle fall.	trailer
Code/Standard Certified to NZTA Rule 4(00): 2002 General Drawing Number(s)		Component Load Rating(s) X1 = 4.25m / Y2 = 35tonnes /	1 = 35 tannes 1 x 2 = 4.25m
Supporting Documents SRT Complic Special Conditions	mee Ce	+ # \$539	
A3	About		
	Above.	Hubodometer Reading (whice	never comes first)
	y Vehicle d a current valid ned vehicle stion, and this Land Transport my Deed of le information	Designer's ID (if certified by a number of the late) Inspector's / Delegate's Sign Delegate's Name (PRINT IN CALL) Date 18/2/2013	nanufocturer].

Form ID

New Zealand Government

LT400

DOMETT TRUCK & TRAILER LTD **Hewletts Road** PO Box 5215 Mount Maunganui **NEW ZEALAND**

PHONE 07 575 5139 07 575 5137 FAX



Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Hohepa Whanau Ltd

Address:

SRT Compliance Certificate no:

S539

Vehicle Identification No.(VIN):

7A9E20016D1023129

Vehicle chassis No:

1129

Current vehicle registration:

Type of vehicle:

Full-Trailer

No of axles in front set:

No of axles in rear set: 3

Deck length of vehicle:

11.3 metres

Maximum height of load or vehicle body:

4.25 metres

Front suspension type: * * *

User Defined

Rear suspension type:

User Defined

I, Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui certify that at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load

Uniform

Description: Assumes load mass is centred midway

type:

density

vertically between load bed and load

height.

At a max, load height of 4.25 metres and a max, allowable gross mass of 35 tonnes, the SRT is 0.35g

This vehicle meets or exceeds the minimum SRT standard of 0.35g.

Results of SRT test to be displayed on Certificate of Loading

3 6 10

X1 = 4.25 metres / Y1 = 35 tonnes; Y2 = 35 tonnes / X2 = 4.25 metres.

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c

Summary Input Data used for calculation.

Tyre Data:

Axle		Tyre Size:	Tyre Configuration:
1		19.5	Dual
2		19.5	Dual
3		19.5	Dual
4		19.5	Dual
5 +	7×1	9.5	Dual

Body Style is Standard

-- T. M

Mass and Suspension Data:

Inputs	Front ®	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	12640	14680
Tare mass (kg):	3360	4320
Average load bed height (m):	1.08	
Average load height (m):	4.25	
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.98	0.98
Lash (mm):	104	104
Suspension brand/model:	ROR CS9	ROR CS9
Roll stiffness/axle (Nm/radian):	2197000	2197000
Spring stiffness/spring (N/m):	128000	128000
Roll centre height from axle (m):	0.035	0.035

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle

Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule; and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Vehicle Inspector/Inspecting Organisation No

BJS

SRT Compliance Certificate no:

Name: Bruce Sutton

10 10 " 1

7 10 TO 10 76

1 ME 2 ME

Date: 18/2/2013

\$539