

Heavy Vehicle Specialist Certificate

Must be presented to a Transport Service Delivery Agent Heavy Vehicle Specialist Inspector and Inspecting Organisation

BRUCE SU			F	355
Vehicle Registration*	VIN / Chassis Nu	ımher		
venicle negistration			170102	3 184
Component being certified:	Chassis N	Modification	Load Anchorage	Log Bolsters
	Towing C	onnection	Brakes	SRT
Contification Cotons	PSV Stabi	lity	PSV Rollover	Swept Path
Certification Category HVS2	PBS	-		
Description of Work Cert.C	7 SRT -	5 axe	full Tail	er
il-crais knot skiles				
1) 1) in minume		/	Class (CAS) on the season beautiful and the season of the	
201		territoria il	CHINA (New and Control of the	
managara rational and the second				
Code/Standard Certified to		Component L	oad Rating(s)	
NZTA Ryk 41001.	2002	X1=4.	25m /1=29	T
General Drawing Number(s)			5T/X2 = 3.9 "	
D. N. S III S III B. SECRE		Load -	Type: Unitom	Density
Supporting Documents	()	0 1	" 0-1=	,
SRT	Compliance	Cert	# 5565	
Scannial Conditions			No. of the service supplementation to	
*Special Conditions	bne			
			The second secon	
Certification Expiry Date (if applicable)	or	Hubodometer	Reading (whichever comes firs	t)
S. Lemma				لال الالا
Declaration				
I the undersigned, declare that I am th	e Heavy Vehicle	Designer's ID	(if certified by a manufacturer)	
Specialist Inspector identified above ar	and the second s	Inspector's / I	Delegate's Signature	
valid appointment. I certify that the ab		Blue		
component's design, manufacture and certification complies in all respects w		*Delegate's/In	spector's Name (PRINT IN CAPS) ID number
Rule Vehicle Standards Compliance 20	20 H		100 0	
Appointment. To the best of my knowledge of the state of the section of the secti		Date i//o/a	Number	
contained in this Certificate is true and	correct.	16/9/20	44	5104
COF Vehicle Inspector ID:	COF Vehicle Inspec	tor Signature:	Date	

All fields excluding those marked with * must be completed before this certificate can be accepted.

PHONE 07 575 5139 FAX 07 575 5137



www.domett-trailers.co.nz

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Riordan & West Ltd

Address:

SRT Compliance Certificate no:

S565

Vehicle Identification No.(VIN):

7A9E30017D1023184

Vehicle chassis No:

1184

Current vehicle registration:

Type of vehicle:

Full-Trailer

No of axles in front set:

2

No of axles in rear set:

3

Deck length of vehicle:

9.52 metres

Maximum height of load or vehicle body:

4.25 metres

Front suspension type:

User Defined

Rear suspension type:

User Defined

I, Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui certify that at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max, load height of 4.25 metres and a max, allowable gross mass of 35 tonnes, the SRT is 0.32g. This vehicle fails to meet the minimum SRT standard of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.25 metres, the maximum allowable gross mass is 29 tonnes.
- or (b) At maximum gross mass of 35 tonnes, the maximum allowable load height is 3.9 metres.

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)	
35	3.9	
34	3.95	
33	4	
32	4.06	
31	4.11	
30	4.17	
29	4.24	
28	4.25	

Note: Calculated load heights greater than the legal limit of 4.25m have been set to 4.25m

Results of SRT test to be displayed on Certificate of Loading	
X1 = 4.25 metres / Y1 = 29 tonnes; $Y2 = 35 tonnes / X2 = 3.9 metres$.	

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual
2	19.5	Dual
3	19,5	Dual
4	19.5 _{14.}	Dual
5	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs i g	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	12280	15320
Tare mass (kg):	3720	3680
Average load bed height (m):	1.21	
Average load height (m):	4.25	
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90 -	90 -
Suspension brand/model:	SAF INTRADISC 1U25/2000RZ	SAF INTRADISC 1U25/2000RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Rol centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Name: Bruce Sutton

可能 集命员

Vehicle Inspector/Inspecting Organisation No BJS

Date: 16/9/2013

SRT Compliance Certificate no.

S565