

Static Roll Threshold Compliance Certificate

Name of vehicle owner: Tapper Transport Ltd
 Address:
 SRT Compliance Certificate no: S616
 Vehicle Identification No.(VIN): 7A9E15012E1023226
 Vehicle chassis No: 1226
 Current vehicle registration:
 Type of vehicle: Full-Trailer
 No of axles in front set: 2 No of axles in rear set: 3
 Deck length of vehicle: 12.65 metres
 Maximum height of load or vehicle body: 4.25 metres
 Front suspension type: User Defined
 Rear suspension type: User Defined

I, **Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui** certify that at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max. load height of 4.25 metres and a max. allowable gross mass of 35 tonnes, the SRT is 0.33g

This vehicle fails to meet the minimum SRT standard of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.25 metres, the maximum allowable gross mass is 30 tonnes.
- or (b) At maximum gross mass of 35 tonnes, the maximum allowable load height is 3.98 metres.

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)
35	3.98
34	4.03
33	4.08
32	4.12
31	4.18
30	4.24
29	4.25

Note: Calculated load heights greater than the legal limit of 4.25m have been set to 4.25m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.25 metres / Y1 = 30 tonnes ; Y2 = 35 tonnes / X2 = 3.98 metres.

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c

Summary Input Data used for calculation.

Tyre Data:


Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual
2	19.5	Dual
3	19.5	Dual
4	19.5	Dual
5	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	12820	15280
Tare mass (kg):	3180	3720
Average load bed height (m):	1.10	
Average load height (m):	4.25	
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90	90
Suspension brand/model:	SAF INTRADISC IU28-2005RZ	SAF INTRADISC IU25-2000RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Roll centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under *section 2 of Land Transport Rule: Vehicle Standards Compliance 2002*. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed: 

Name: **Bruce Sutton**

Vehicle Inspector/Inspecting Organisation No **BJS**

Date: **19/2/2014**

SRT Compliance Certificate no:

S616