

New Zealand Government

Heavy Vehicle Specialist Certificate

Must be presented to a Transport Service Delivery Agent Heavy Vehicle Specialist Inspector and Inspecting Organisation

Version No. 10/13

Heavy Vehicle Specialist Inspector's or Manufacturing Inspecting Organisation's Name (PRINT IN CAPS) BRUCE SUTTON	BIS
Vehicle Registration* VIN/Chassis Number 7 A 9 E 2 5 0 1 0 E 1 0	23318
Component being certified: Chassis Modification Load Anchorage Towing Connection Brakes	Log Bolsters
Certification Category HVS2 PSV Stability PSV Rollover	Swept Path
Description of Work Certify SRT- 5 axke full trailer	
Composet Load Beting(c)	
Code/Standard/Rule Certified to NZTA Rule 41001: 2002 General Drawing Number(s) Component Load Rating(s) $X1 = 4 \cdot 25m / Y1 = 2$ $Y2 = 35T / X2 = 3$ Supporting Documents	98m
SRT Compliance Cert # S673	
Special Conditions* AS Above	
Certification Expiry Date (if applicable) Or Hubodometer Reading (whichever comes for the company of the compa	
Designer's ID (if different from inspector below I the undersigned, declare that I am the Heavy Vehicle Specialist Inspector identified and I hold a current valid appointment. I certify that the above mentioned vehicle component's design, manufacture and installation, and this certification complies in all respects with the Land Transport Rule: Vehicle Standards Compliance 2002 and my Appointment. To the best of my knowledge the information contained in the Certificate is true and correct. Designer's ID (if different from inspector below Inspector's Signature Inspector's Name (PRINT IN CAPS) Date Number Place Place Place Number Place Place Number Place Place Number Place Place Number Place Place	ID Number
CoF Vehicle Inspector ID CoF Vehicle Inspector Signature Date	110040

Form ID

LT400

PHONE 07 575 5139

07 575 5137



Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Address:

SRT Compliance Certificate no:

Vehicle Identification No.(VIN):

Vehicle chassis No:

Current vehicle registration:

Type of vehicle:

No of axles in front set:

Deck length of vehicle:

Maximum height of load or vehicle body:

Front suspension type:

Rear suspension type:

Stocklines Ltd

S673

7A9E25010E1023318

1318

Full-Trailer

No of axles in rear set:

3

11.28 metres

4.25 metres

User Defined

User Defined

I, Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max. load height of 4.25 metres and a max. allowable gross mass of 35 tonnes, the SRT is 0.33g This vehicle fails to meet the minimum SRT standard of 0.35g. It will meet the standard if:

- At maximum load height of 4.25 metres, the maximum allowable gross mass is 29.6 tonnes.
- At maximum gross mass of 35 tonnes, the maximum allowable load height is 3.98 metres. or (b)

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)	
35	3.98	
11000 34	4.03	
33	4.07	
32	4.11	
18446 31	4.17	
30	4.22	
1880 29	4.25	

Note: Calculated load heights greater than the legal limit of 4.25m have been set to 4.25m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.25 metres / Y1 = 29 tonnes; Y2 = 35 tonnes / X2 = 3.98 metres.

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
	19.5	Dual
2 5010	19.5	Dual
3	19.5	Dual
<u></u>	19.5	Dual
5	C 019.5 0 C 0	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	13220	15840
Tare mass (kg):	2780	3160
Average load bed height (m):	1.04	
Average load height (m):	4.25	
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90	90
Suspension brand/model:	SAF Intradisc IU28- 2005RZ	SAF Intradisc IU28- 2005RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Roll centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:_

Vehicle Inspector/Inspecting Organisation No BJS

SRT Compliance Certificate no:

Name: Bruce Sutton

Date: 9/12/2014

S673

