

New Zealand Government

Heavy Vehicle Specialist Certificate

Must be presented to a CoF (Heavy) Inspecting Organisation Heavy Vehicle Specialist Inspector and Inspecting Organisation

Version No. 08/14

Heavy Vehicle Specialist Inspector's or Manufacturing Inspecting Organ BRUCE SUTTON	isation's Name (PRINT IN CAPS)	BJS	
Vehicle Registration* VIN/Chassis Nu	E 2 5 0 1 4 E 1 0	023323	
Component being certified:	odification Load Anchorage	Log Bolsters	
Towing Co.	nnection Brakes	SRT	
Certification Category HVS 2 PBS Description of Work Certify SRT- 5 ax	le full trailer	Swept Path	
Cering skir sax	10/11/100		
Code/Standard/Rule Certified to	Component Load Rating(s)		
NZTA Rule 41001: 2002	XI=4.25m/11	= 29 T	
General Drawing Number(s)	12=35T/X2=	3-97m	
	Load Type: Uni	form Density	
Supporting Documents SRT Comphance Cet.	# S683		
JIL SON PROMICE COST			
Special Conditions*			
As Above			
Certification Expiry Date (if applicable)	Hubodometer Reading (whichever comes	first)	
Declaration	Designer's ID (if different from inspector belo	(wc	
I the undersigned, declare that I am the Heavy Vehicle Specialist			
Inspector identified and I hold a current valid appointment. I certify that the above mentioned vehicle component's design,	Inspector's Signature		
manufacture and installation, and this certification complies in all respects with the Land Transport Rule: Vehicle Standards	Inspector's Name (PRINT IN CAPS)	ID Number	
Compliance 2002 and my Appointment. To the best of my knowledge the information contained in the Certificate is true			
and correct.	Date 22/1/2015. Num	498903	
CoF Vehicle Inspector ID CoF Vehicle Inspec			
All fields excluding those marked with * must be completed before this certificate can be accepted.			

LT400

Form ID

PHONE 07 575 5139 07 575 5137



www.domett-trailers.co.nz

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Address:

SRT Compliance Certificate no:

Vehicle Identification No.(VIN):

Vehicle chassis No:

Current vehicle registration:

Type of vehicle:

No of axles in front set:

Deck length of vehicle:

Maximum height of load or vehicle body:

Front suspension type:

Rear suspension type:

GVT Landline Ltd

S683

7A9E25014E1023323

1323

Full-Trailer

No of axles in rear set:

3

ko)ko)ko

10.67 metres

4.25 metres

User Defined

User Defined

I, Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max, load height of 4.25 metres and a max, allowable gross mass of 35 tonnes, the SRT is 0.33g This vehicle fails to meet the minimum SRT standard of 0.35g. It will meet the standard if:

- At maximum load height of 4.25 metres, the maximum allowable gross mass is 29.4 tonnes.
- At maximum gross mass of 35 tonnes, the maximum allowable load height is 3.97 metres. or (b)

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)	
35	3.97	
34	4.02	
33	4.07	
32	4.1	
15945 31	4.15	
30	4.21	
1990 29	4.25	

Note: Calculated load heights greater than the legal limit of 4.25m have been set to 4.25m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.25 metres / Y1 = 29 tonnes; Y2 = 35 tonnes / X2 = 3.97 metres.

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c



Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual 1100
2	19.5	Dual
3	19.5	Dual
\wedge_4	19.5	Dual
5	19.5	Dual
5	_ 19.5_	Duai

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	13240	-15940
Tare mass (kg):	2760	3060
Average load bed height (m):	1.04	
Average load height (m):	4.25	
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90	90
Suspension brand/model:	SAF Intradisc IU28- 2005RZ	SAF Intradisc IU28- 2005RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Roll centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed: 100

Vehicle Inspector/Inspecting Organisation No BJS

SRT Compliance Certificate no:

Name: Bruce Sutton

Date: 22/1/2015

S683



