

Heavy Vehicle Specialist Certificate

Heavy Vehicle Specialist Inspector and Inspecting Organisation

Heavy Vehicle Specialist Inspector's Name (PRINT IN CAPS)	PRATT		TRSP
	ssis Number	1640	023/90
Component being certified:	assis Modification	Load Anchorage	Log Bolsters
HUEK Description of Work	wing Connection	Brakes	SRT
Certify to Broke Rule	32015		
ode/Standard Certified to WZHUBRUE Schedule 5 eneral Drawing Number(s)	Component	Load Rating(s)	
NA			
Brake Cert No RP100913			
PREU VANS Exemption No	HVB10/2	7/	
Special Conditions			,
EBS Control Worning Lomp Mu.	stillomirale	when ignora	on switchedon a
extinguish immediates OR	When wehr	le reaches 7	Kph.
ertification Expiry/Date (if applicable)		er Reading (whichever co	
NA			
Declaration			
	Designer's II	(if certified by a manufact	urer)
I the undersigned, declare that I am the Heavy Vehicle Specialist Inspector identified above and I hold a current val	id		
appointment. I certify that the above mentioned vehicle	Inspector's /	Dalegate's Signature	
component's design, manufacture and installation, and this	*Delegate's	Name (PRINT IN CAPS)	
certification complies in all respects with the Land Transport	Delegates	Marine (Praint IN CAPS)	
Rule Vehicle Standards Compliance 2002 and my Deed of Appointment. To the best of my knowledge the information	Date /	Num	ber
contained in this Certificate is true and correct.	21/09	2010	351750

Form ID

New Zealand Government

LT400

Version No. 01/09



Document: Exemption: B1081485 HVB10/271 Level 9, PSIS House 20 Ballance Street PO Box 5084 Lambton Quay Wellington 6145 New Zealand T 64 4 894 5200 F 64 4 894 3305 www.nzta.govt.nz

EXEMPTION FROM SPECIFIED REQUIREMENTS OF LAND TRANSPORT RULE: Heavy-vehicle Brakes 2006, Rule 32015

Pursuant to Section 166(1) of the Land Transport Act 1998, and pursuant to the powers delegated to me, I Eugene Girardin, Vehicles Unit Engineer, hereby exempt the motor vehicle specified in Schedule 1 hereto from the section of Land Transport Rule: Heavy-vehicle Brakes 2006 (the Rule) listed in Schedule 2, subject to the conditions specified in Schedule 3.

SCHEDULE 1:

Make/Model:

Domett Truck & Trailer Ltd, 4 Axle Full Trailer

VIN/CHASSIS:

7A9D10016Y0023190

SCHEDULE 2: - Exempted Requirement

Section 2.3(9); The parking brake of a vehicle, whether or not it is being operated as a combination vehicle, must be able to be applied by the driver from the normal driving position using one control only.

SCHEDULE 3: - Conditions of this exemption:

- The vehicle must be fitted with a Wabco park-release emergency valve (PREV), Part Number: 971 002 900 0.
- The vehicle must be fitted with the Wabco PREV name plate, Part Number 971 002 103 4, adjacent to the PREV.
- The vehicle must still be fitted with a parking brake that complies with all parking brake requirements in the Rule other than the requirement in Clause 2.3(9) of the Rule.
- 4) The installation of the PREV must be approved in writing by Transport Specialties Limited (Transpecs) or an NZ Transport Agency appointed HVEK certifier acting on behalf of, and under instruction from, Transpecs; Transpecs must keep a written record of all approvals.
- An HVEK certifier in 4) must be fully trained in end of line procedures for Wabco electronically controlled braking systems
- 6) Transpecs must provide full operator training in the use of the PREV and furnish the operator with full written operating instructions for the PREV.
- The vehicle must not be modified in any way while operating under this exemption.
- This original exemption must be kept by Transport Specialties LTD.
- A copy of this exemption (printed on a silver WABCO Sticker) must be affixed to the exempted vehicle as close to the WABCO PREV as possible.
- 10) The sticker in 8) must be legible and include all printed area's of this original exemption letter.
- This exemption can be revoked at any time in writing by the NZ Transport Agency.

Signed at Wellington this 26th day of July 2010

Gradi

Eugene Girardin Engineer

Vehicles Unit

NOTICE TO VEHICLE OPERATOR

This trailer is equipped with an Electronic Brake System.

To comply with the New Zealand Heavy Vehicle Brake RULE, it must be used only in conjunction with a truck/tractor equipped with a 5 or 7 pin ABS/EBS power supply socket.

Failure to connect to such supply invalidates Brake Rule compliance.

The trailer ABS/EBS warning light on the towing vehicle dashboard must illuminate when the ignition is switched on and extinguish when the vehicle is in motion.

If the light does not illuminate when ignition is switched on, the system must be checked. If the light remains illuminated when the vehicle is in motion, Brake Rule compliance is compromised. Repairs must be made as soon as possible.

NB;

If this vehicle is fitted with mechanical (spring) suspension, the load sense valving has been adjusted to suit exactly the performance of the original springs. In event of replacement being required, original equipment springs **must** be fitted to ensure correct ongoing operation. Fitment of non genuine springs can affect operation and therefore, compliance.

If you are unsure of your responsibilities and/or obligations. please contact either the vehicle manufacturer or myself.

R S Pratt

(TRSP HVEK 09 980 7300)

NOTICE TO VEHICLE OPERATOR

THIS VEHICLE HAS A BRAKE SYSTEM WHICH HAS BEEN DESIGNED AND FITTED IN ACCORDANCE WITH THE NEW ZEALAND HEAVY VEHICLE BRAKE RULE 32015: SCHEDULE 5.

IF THIS VEHICLE IS OPERATED IN CONJUNCTION WITH NON-CODED VEHICLES, THERE MAY BE OPERATIONAL FACTORS WHICH NEED TO BE TAKEN INTO CONSIDERATION.

PLEASE REFER TO THE CERTIFIER FOR FURTHER INFORMATION.

EXCERPT FROM NZ HEAVY VEHICLE BRAKE RULE 32015

10.1 Responsibilities of operators

A person who operates a vehicle must ensure that the vehicle complies with this Rule

10.2 Responsibilities of repairers

A person who repairs or adjusts a brake must ensure that the repair or adjustment:

- (a) does not prevent the vehicle from complying with the rule: and
- (b) complies with Land Transport Rule: Vehicle Repair 1998.

10.3 Responsibilities of modifiers

A person who modifies a vehicle so as to affect the braking performance of the vehicle must:

- (a) ensure that the modification does not prevent the vehicle from complying with this rule: and
- (b) notify the operator that the vehicle must be inspected and. If necessary. Certified by a person or organisation appointed to carry out specialist inspection and certification of heavy vehicle brakes.

10.5 Responsibilities of manufactures and retailers

A person may manufacture, stock, or offer for sale a brake or its components. Intended for fitting to a vehicle to be used on New Zealand roads, only if that brake or component:

- (a) complies with this Rule: and
- (b) does not prevent a repair to a vehicle, its structure, systems, components and equipment from complying with this Rule.

IF YOU ARE UNSURE ABOUT YOUR RESPONSIBILITIES, PLEASE CONTACT THE VEHICLE MANUFACTURER, OR MYSELF.

COMPLAINTS. Complaints and Warranty issues which relate to Brake Certification will be acknowledged within 7 working days and a resolution proposed within 25 working days. Resolution of complaints and Warranty issues is subject to Transpecs Warranty policy. Customers have the right to appeal to the Land Transport Safety Authority if dissatisfied with a Compliance issue. (refer LTNZ Deed Of Appointment Para 47.4) Land Transport NZ Helpdesk 0800 699 000

R S PRATŤ (TRSP HVEK)

V	VA	B	CC				TR	AILE	RI	EBS-	E	GGVS/A		TB 2007 -	019.00
MANUFAC CONSTRU	TURER	DO	METT					GIO		Pin1		Pin3		Pi	n4
TYP			AAV	TANK	ED			1							77.5
TYPE			444	IAN	ER			2						-	-
CHASSIS	G IDENTINA. NUMBER DE CHASSIS		7A9E	1001	6Y002	3190		3		ALS2		ALS2		-	-
	RECHAUNGS AF		TP50	1420				4							-
	E FREINAGE NO AHNEZAM, (-4)	_	11 00	720	ABS-8yslem	V-10-10-10-10-10-10-10-10-10-10-10-10-10-		5	- 1	DIAG		DIAG		DI	AG
POLE WHI	HEL TEETH od	14	90	90	ABS-System Système ABS	4S/3M		6						-	-
RSS RSS RSS	Eistlachtereife Single Tire Monte zimple	eg .		Limkethse Steering as Escies vira	ile			7		***				-	-
	Zwittingsterei Twin Tire Monte jamelés	0.0	X	Kippkritisc Critical Tra Váltácule cr								-			
Subs	ystems				I/O					Π	H		Y	7	
	T									_				(0)	(bar)
	_					••	•			00			/8\ T	(4)	(vai)
	pm (t		6.5	pı	m (bar)	0.7	2.0		6.5	-		쁔	OI.	1.0	Pz
AXLE	pm (t		6.5		10		2.0		6.5 pz	-	TYP	(mm)	(mm)	1.0	12000
ACHRE AXLE ESSIEU	-		(0)) 14	[Rej) =	3				-	TYP	(mm)	S-50	1.0	Pz
ESSEU	+ (*a)	oar)	1.5	700	1 ^(kg) =	3 0.4	(0)		pz		TYP TYPE		(mm)	1.0 TR (Pz (daN)
AXLE ESSEU	1400	0.6	1.5	700	00 4.6 00 4.6	3 0.4 3 0.4	(0)		pz.		TYP TYPE 14	64	(mm)	1.0 TR (Pz (daN)
1 2	1400 1400	0.6 0.6	(O) 1.5 1.5 1.2	700 5 700 5 700 2 700	00 4.6 00 4.6 00 4.6	3 0.4 3 0.4 3 0.4	(O) 1.2 1.2		pz 5.8 5.8		14 14	64 64	(mm) 69 69	1.0 TR (daN)

.



P.O.Box 98-971 South Auckland Mail Centre Ronald Stuart Pratt (TRSP)

DATE	21/09/2010	21/09/2010 TYPE APPROVED	SAF4AEBS-E
CERTIFICATE No	RP100913		HVB10/271
VIN No	7A9D10016Y0023190	3190	
BRAKE CHAMBERS FRONT 14TSE64mm	14TSE64mm		
BRAKE CHAMBERS REAR 14/16TSE 64mm LOAD SENSED	14/16TSE 64mm	LOAD SENSED	YES EBS CONTROL
SLACK LENGTH FRONT	Disc	TYRE SIZE FRONT	265/70R19.5
SLACK LENGTH REAR	Disc	TYRE SIZE REAR	265/70R19.5
THIS VEHICLE COMPLIES WITH N.Z.	VITH N.Z	LINING MATERIALFRONT	Jurid 539
HVBR 32015/2 SCHEDULE 5		LINING MATERIAL REAR Jurid 539	Jurid 539