

002 19:43 25/1/2001 DOMETT4A.DT4
 STATEMENT OF COMPLIANCE WITH THE NEW ZEALAND HEAVY VEHICLE BRAKE CODE

VEHICLE TYPE : FULL TRAILER
 MAKE : DOMETT. MODEL : D2001.
 SERIAL NUMBER : 222. GVM (on road) : 29,000 Kg.
 GVM (off road) : 29,000 Kg. GCM : N/A.
 UNLADEN CoG HEIGHT : 0.750 WHEELBASE : 5.200
 UNLADEN MASS, FRONT : 3.320 UNLADEN MASS, REAR : 4.060
 PAYLOAD : 21.62
 PAYLOAD CoG HEIGHT : 2.000 POSITION : 2.513 RANGE :
 FRONT SUSPENSION TYPE : DUAL AXLE REAR SUSPENSION TYPE : DUAL AXLE
 REACTIVE/NONREACTIVE : NONREACTIVE. REACTIVE/NONREACTIVE : NONREACTIVE.
 SYSTEM PRESSURE: MAXIMUM OPERATING Pm : N/A.
 GOVERNOR CUTIN Pg : N/A.
 TIME Pg to Pm : N/A.

AXLE	COUPLING THRESHOLD kPa	BRAKE FORCE kN/kPa	TYRE SIZE mm	FRICTION MATERIAL		
				MAKE	ID NUMBER	COF
1	76.10	0.095	408.0	TEXTAR.	T090 FF.	0.450
2	76.10	0.095	408.0	TEXTAR.	T090 FF.	0.450
3	63.41	0.073	408.0	TEXTAR.	T090 FF.	0.450
4	63.41	0.073	408.0	TEXTAR.	T090 FF.	0.450

AXLE	BRAKE TYPE	DRUM DIAMETER	CHAMBER SIZE	SLACK LENGTH	SPRING FORCE
1	S, CAM. (BPW)	420.0	140.6	122.0	0.000
2	S, CAM. (BPW)	420.0	140.6	122.0	0.000
3	S, CAM. (BPW)	420.0	140.6	122.0	5.940
4	S, CAM. (BPW)	420.0	140.6	122.0	5.940

TRAILER

VALVE TYPE	MAKE	MODEL/VERSION
RELAY 1	BENDIX.	R-12 (38KPA CRACK)
RELAY 2	BENDIX.	R-12 (28KPA CRACK)
SPRING BRAKE VALVE	BENDIX.	SR-5 P/No:102831.
QUICK RELEASE VALVE	N/A.	N/A.
PILOT	BENDIX.	SC-3 (TANK PROTEC)
OTHER	BENDIX.	F.R.V.RATIO SET @75%
OTHER	BENDIX.	PP-V EMERG RELEASE

I, the undersigned do hereby certify that the vehicle identified above complies with all requirements of the current New Zealand Heavy Vehicle Brake Code.

Date : 25/1/2001.

Signed : *R.A. Finch*

Certifier's Identification

Name : R.A.FINCH. (RF)

Phone : (07)347-7872.

Postal Address : BNT COMMERCIAL.
: P.O.Box 233.
: ROTORUA.

Fax : (07)346-1566.

Position : HVEB CERTIFIER. (R.F)

Modification

I, the undersigned do hereby re-certify the vehicle identified above, as modified complies with all requirements of the current New Zealand Heavy Vehicle Brake Code.

Date :

Signed :

Certifier's Identification

Name :

Phone :

Postal Address :

Fax :

Position:

002 19:39 25/1/2001 DOMETT4A.DT4

FOODSTUFFS (AUCKLAND) LTD, AUKLAND. 25/1/01
DOMETT 4 AXLE CURTAINSIDER TRAILER.
Job/No: 1094, S/No: 222, Rego:
Vin/No: 7A9D20018Y0023222.

VEHICLE TYPE : FULL TRAILER
FRONT SUSPENSION TYPE : DUAL AXLE
REAR SUSPENSION TYPE : DUAL AXLE

TARE MASS ON THE FRONT SUSPENSION OF THE VEHICLE : 3.320 tonnes
TARE MASS ON THE REAR SUSPENSION OF THE VEHICLE : 4.060 tonnes
VEHICLE WHEELBASE : 5.200 m
CENTRE OF GRAVITY HEIGHT FOR THE UNLADEN VEHICLE : 0.750 m
MASS OF THE LOAD ON THE VEHICLE : 21.62 tonnes
LENGTH FROM FRONT SUSPENSION TO LOAD CoG : 2.513 m
HEIGHT OF THE LOAD CoG ABOVE GROUND : 2.000 m

Laden mass on the front suspension = 14.49
Laden mass on the rear suspension = 14.50

AXLE TYPE	NO. OF VALVES	RATIO VALVE	INSHOT PRESSURE	RATIO OUT/IN	COUPLING PRESSURE 100Nm DRUM TORQUE
1	1	0	0.000	0.000	76.10
2	2	1	70.00	0.750	63.41

AXLE TYPE	VALVE NO.	CRACKING PRESSURE	PRESSURE IN kPa	PRESSURE OUT kPa
1	1	38.00	800.0	800.0
2	1	0.000	650.0	505.0
2	2	28.00	275.0	279.0

AXLE TYPE	LINING CoF	CHAMBER AREA cm ³	ADJUSTER LENGTH mm	TYRE RADIUS mm	BRAKE DRUM RADIUS mm
1	0.450	140.6	122.0	408.0	210.0
2	0.450	140.6	122.0	408.0	210.0

AXLE TYPE	S-CAM RADIUS mm	% BRAKE EFFICIENCY	CHAMBER PRESSURE 100Nm DRUM TQUE.
1	14.00	0.800	40.00
2	14.00	0.800	40.00

VEHICLE BRAKE FORCE/TONNE AT 500kPa = 5.06kN/tonne

AXLE NO.	AXLE TYPE	EMERGENCY PRESSURE kPa	PARKING FORCE kN
1	1	345.0	0.000
2	1	345.0	0.000
3	2	345.0	5.940
4	2	345.0	5.940

STOPPING DISTANCE FOR EMERGENCY PRESSURE = 8.93 m

STOPPING DISTANCE FOR SPRING BRAKES = 14.29 m

THE PARKING BRAKES WILL HOLD THE VEHICLE ON A 1 IN 3.91 SLOPE

FOODSTUFFS (AUCKLAND) LTD, AUKLAND. 25/1/01

