

New Zealand Government

Heavy Vehicle Specialist Certificate

Must be presented to a Transport Service Delivery Agent Heavy Vehicle Specialist Inspector and Inspecting Organisation

Heavy Vehicle Specialist Inspector's or Manufacturing Inspecting Organisation's Name (PRINT IN CAPS) BRUCE SUTTON	B 75
Vehicle Registration* VIN/Chassis Number 7A9D20017B00	023932
Component being certified: Chassis Modification Load Anchorage	Log Bolsters
Towing Connection Brakes	SRT
Certification Category HVS 2 PSV Stability PSV Rollover PBS Description of Work Certify SRT- 5 axle full frailer	Swept Path
	2. 1
Code/Standard/Rule Certified to NZTA Rule 41001: 2002 General Drawing Number(s) Component Load Rating(s) X1 = 4-25m / 1 = 3 Y2 = 35T / X2 = 4 Load Type: Unfo	·05m
Supporting Documents SRT Compliance Cet # S647	
Special Conditions* As Above	
Certification Expiry Date (if applicable) Or Hubodometer Reading (whichever comes Designer's ID (if different from inspector below	
I the undersigned, declare that I am the Heavy Vehicle Specialist Inspector identified and I hold a current valid appointment. I certify that the above mentioned vehicle component's design, manufacture and installation, and this certification complies in all respects with the Land Transport Rule: Vehicle Standards Compliance 2002 and my Appointment. To the best of my knowledge the information contained in the Certificate is true and correct. Inspector's Signature Inspector's Signature Inspector's Name (PRINT IN CAPS) Date Numi	1D Number ber 470917
CoF Vehicle Inspector ID CoF Vehicle Inspector Signature Date All fields excluding those marked with * must be completed before this certificate can be	accented.

Form ID

LT400

Version No. 10/13

PHONE 07 575 5139

07 575 5137 FAX



www.domett-trailers.co.nz

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Address:

SRT Compliance Certificate no:

Vehicle Identification No.(VIN):

Vehicle chassis No:

Current vehicle registration:

Type of vehicle:

No of axles in front set:

Deck length of vehicle:

Maximum height of load or vehicle body:

Front suspension type:

Rear suspension type:

K&S Freighters Ltd

S647

7A9D20017B0023932

932

Full-Trailer

No of axles in rear set:

3

11.3 metres

4.25 metres

User Defined

User Defined

I, Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max, load height of 4.25 metres and a max, allowable gross mass of 35 tonnes, the SRT is 0.33g This vehicle fails to meet the minimum SRT standard of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.25 metres, the maximum allowable gross mass is 31.3 tonnes.
- At maximum gross mass of 35 tonnes, the maximum allowable load height is 4.05 metres.

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)		
35	4.05		
11000 34	4.1		
33	4.14		
32	4.2		
31	4.25		

Note: Calculated load heights greater than the legal limit of 4.25m have been set to 4,25m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.25 metres / Y1 = 31 tonnes; Y2 = 35 tonnes / X2 = 4.05 metres.

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c



Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1 5000	19.5	Dual 1100
2	19.5	Dual
3	19.5	Dual
4	19.5	Dual
5	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	12400	14980
Tare mass (kg):	3600 4751	4020
Average load bed height (m):	1.08	
Average load height (m):	4.2	25
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90	90
Suspension brand/model:	SAF Intradisc IU28- 2005RZ	SAF Intradisc IU28- 2005RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Roll centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Vehicle Inspector/Inspecting Organisation No BJS

SRT Compliance Certificate not

Name: Bruce Sutton

Date: 30/7/2014

S647



