

Heavy vehicle specialist certificate Must be presented to a CoF (heavy) inspecting organisation if not entered into LANDATA

Plate number (optional)	VIN/	hassis	numb	er											
ate named (aptona)		A 9		2	0	0	1 5	P	2	0	2	3	3	4	6
Make DOMETT	Com	ponent	t being	certifi	ed:		Cha	ssis					Load	d ancl	norag
Model (optional) 2023 E2001 PH]1	og bol	sters				Tow	ng con	necti	on			Brak	es	
Certification category	X	SRT					PSV	stabilit	Ty				PSV	rollo	ver
HVS2		Swept p	path				PBS								
Description of work															
CERTIFY SRT - 5 AXLE FUL	LL T	RAI	LEF	7											
							.001	n / Y			ル				
upporting documents SRT COMPLIANCE CERT # S pecial conditions (optional) AS ABOVE	3139	1		-	Y2 :	= 3	5t / TYF	X2 =	= 4.	01r	n	ID	EN	SIT	Υ
upporting documents SRT COMPLIANCE CERT # S	6139		or	Hub	Y2 =	= 3	5t /	X2 = PE: U	= 4. UNI	01r FO	n RM	ID	EN	SIT	Y

Te Kāwanatanga o Aotearoa New Zealand Government

All fields are mandatory unless otherwise stated.

Form ID

LT400

Version No. 10/23

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Hilton Haulage

Address:

SRT Compliance Certificate no:

S1391

Vehicle Identification No.(VIN):

7A9E20015P2023346

Vehicle chassis No:

2346

Current vehicle registration:

Type of vehicle:

Full-Trailer

No of axles in front set:

No of axles in rear set:

3

Deck length of vehicle:

11.4 metres

Maximum height of load or vehicle body:

4.3 metres

Front suspension type:

User Defined

Rear suspension type:

User Defined

I, Gerrit Visagie of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142 certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type:

Uniform density

Description:

Assumes load mass is centred midway vertically between

load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 35 tonnes, the SRT is 0.33g

This vehicle fails to meet the minimum SRT target of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.3 metres, the maximum allowable gross mass is 29.8 tonnes.
- or (b) At maximum gross mass of 35 tonnes, the maximum allowable load height is 4.01 metres. The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)
35	4.01
34	4.06
33	4.11
32	4.16
31	4.22
30	4.28
29	4.3

Note: Calculated load heights greater than the legal limit of 4.30m have been set to 4.30m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.3 metres / Y1 = 29 tonnes; Y2 = 35 tonnes / X2 = 4.01 metres.

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:		
1	19.5	Dual		
2	19.5	Dual		
3	19.5	Dual		
4	19.5	Dual		
5	19.5	Dual		

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	12770	15190
Tare mass (kg):	3230	3810
Average load bed height (m):	1.075	
Average load height (m):	4	.3
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90	90
Suspension brand/model:	SAF IU28/2005RZ	SAF IU28/2005RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Roll centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Vehicle Inspector/Inspecting Organisation No GV

SRT Compliance Certificate no:

Name: Gerrit Visagie

Date: 18/10/2023

S1391