

Heavy vehicle specialist certificate Must be presented to a CoF (heavy) inspecting organisation if not entered into LANDATA

ecting of	rganisat	ion's nam	e (PRIN	IT IN CAPS)				ID C	×10	3V		
			0	2 2	P	2	0	2	3	3	9	5
omponei	nt being	certified:		Chass	is				L	oad	anch	norage
Log bo	olsters			Towing	g con	nectio	n		В	rake	es	
SRT				PSV st	abilit	y			P	SV	rollov	/er
Swept	t path			PBS								
1									DE	N.	SIT	Υ_
106												
	or	Hubodo	mete	r reading (whiche	/er com	es first)				
		Designe	r's ID	(if different f	rom insį	oector b	elow)					
ialist . I gn, es ards rue			RF	RIT VIS		S) IE			G Dn	uml V	per]
	Dompone Log be SRT Swept TRA H06	Domponent being Log bolsters SRT Swept path TRAILEF 406	component being certified: Log bolsters SRT Swept path TRAILER Component being certified: Log bolsters SRT Swept path TRAILER Component being certified: Log bolsters SRT Designer Log bolsters Log b	A 9 D 5 0 0 component being certified: Log bolsters SRT Swept path TRAILER Component X1 = Y2 = LOAL LOAL LOAL LOAL Designer's ID Inspector's singles and singles and singles are singles.	A 9 D 5 0 0 2 2 component being certified: Log bolsters SRT PSV st Swept path Component load rating X1 = 4.30m Y2 = 26t / X LOAD TYPI LOAD TYPI Designer's ID (if different fine) Inspector's signature Inspector's name (PRINT GERRIT VIS	A 9 D 5 0 0 2 2 P component being certified: Chassis Log bolsters Towing control SRT PSV stability Swept path PBS TRAILER Component load rating(s) X1 = 4.30m / Y Y2 = 26t / X2 = LOAD TYPE: L LOAD TYPE: L Designer's ID (if different from inspector's signature gn, is lossed on the control of the	component being certified: Log bolsters SRT PSV stability Swept path Component load rating(s) X1 = 4.30m / Y1 = Y2 = 26t / X2 = 4.3 LOAD TYPE: UNII LOAD TYPE: UNII Designer's ID (if different from inspector to the standards) Inspector's signature Inspector's signature GERRIT VISAGIE	Component load rating(s) SRT PSV stability Swept path Component load rating(s) X1 = 4.30m / Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO PSV Stability Component load rating(s) X1 = 4.30m / Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) X1 = 4.30m / Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) X1 = 4.30m / Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) X1 = 4.30m / Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) X1 = 4.30m / Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26 Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) Y1 = 26t / X2 = 4.30m LOAD TYPE: UNIFO Component load rating(s) LOAD TYPE: UNIFO Component load rating(s)	proponent being certified: Log bolsters Log bolsters Component load rating (s) X1 = 4.30m / Y1 = 26t Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFORM The standard of the standard properties of the standard prope	component being certified: Log bolsters Towing connection B SRT PSV stability PBS TRAILER Component load rating(s) X1 = 4.30m / Y1 = 26t Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFORM DE LOAD TYPE: UNIFORM DE Designer's ID (if different from inspector below) Inspector's signature gn, is ards Inspector's name (PPINT IN CAPS) GERRIT VISAGIE Designation of the property of the part of the p	Component being certified: Log bolsters Chassis Load Log bolsters Towing connection Brake SRT PSV stability PSV Swept path PBS TRAILER Component load rating(s) X1 = 4.30m / Y1 = 26t Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFORM DENS LOAD TYPE: UNIFORM DENS Bold Or Hubodometer reading (whichever comes first) Designer's ID (if different from inspector below) ialist Inspector's signature gn, stards Inspector's signature GERRIT VISAGIE ID numles	component being certified: Log bolsters SRT PSV stability PBS Component load rating(s) X1 = 4.30m / Y1 = 26t Y2 = 26t / X2 = 4.30m LOAD TYPE: UNIFORM DENSIT Component load rating(s) A 1 = 4.30m / Y1 = 26t Brakes PSV rollor Component load rating(s) A 2 = 4.30m LOAD TYPE: UNIFORM DENSIT Component load rating(s) A 3 = 9 Brakes PSV rollor Swept path PBS Component load rating(s) A 2 = 4.30m LOAD TYPE: UNIFORM DENSIT Component load rating(s) A 3 = 9 Brakes Brakes PSV rollor Swept path Designer's ID (if different from inspector below) Inspector's signature Brakes Designer's ID (if different from inspector below) Inspector's signature Brakes Designer's ID (if different from inspector below)

Te Kāwanatanga o Aotearoa New Zealand Government

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Hilton Haulage

Address:

SRT Compliance Certificate no:

S1406

Vehicle Identification No.(VIN):

7A9D50022P2023395

Vehicle chassis No:

2395

Current vehicle registration:

Type of vehicle:

Semi-Trailer

No of axles in front set:

0

No of axles in rear set:

4

Deck length of vehicle:

11.99 metres

Maximum height of load or vehicle body:

4.3 metres

Front suspension type:

none

Rear suspension type:

User Defined

I, Gerrit Visagie of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142 certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type:

Uniform density

Description:

Assumes load mass is centred midway vertically between

load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 26 tonnes, the SRT is NaNg

This vehicle fails to meet the minimum SRT target of 0.35g. It will meet the standard if:

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.3 metres / Y1 = 26 tonnes; Y2 = 26 tonnes / X2 = 4.3 metres.

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:			
1	22.5	Large Single			
2	22.5	Large Single			
3	22.5	Large Single			
4	22.5	Large Single			

Body Style is Standard

Mass and Suspension Data:

Inputs	Rear				
Gross mass (kg):	26000				
Payload mass (kg):	21450				
Tare mass (kg):	4550				
Average load bed height (m):	1.39				
Average load height (m):	4.3				
Suspension type:	User Defined				
Suspension track width (m):	1.2				
Lash (mm):	90				
Suspension brand/model:	SAF IU28/2005RB-10				
Roll stiffness/axle (Nm/radian):	1900000				
Spring stiffness/spring (N/m):	470000				
Roll centre height from axle (m):	0.05				

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Vehicle Inspector/Inspecting Organisation No GV

SRT Compliance Certificate no:

Name: Gerrit Visagie

Date: 5/12/2023

S1406